



EFFLUENT TREATMENT PLANT

FOR TWO WHEELER WASHING SEGMENT

EFFLUENT TREATMENT PLANT

FOR TWO WHEELER SEGMENT



Technical Specification

Electrical	: 230 V (± 20%), 50 hz, Single Phase
Flow rate	: 1000 lpm
Suction tubing	: 4/6 mm
Discharge tubing	: 4/6 mm
Dosing rate	: 6 mph at 4 kg/cm ²
Strokes / minute	: Max:400 Min:50
Fuse	: 600 mA
Level switch interlock	: Normally open
Relay output	: Normally open. Closes in case the pump stops for any reason

About ETP

ATS ELGI ETP plays a significant role in the treatment of vehicle washing waste water. Organic matter, inorganic matter, heavy metals, oil & grease, suspended particles and other contaminants are treated in the waste water treatment process of an ETP plant.

Scope of Supply

- Sand Bed filter,
- Activated carbon filter
- Pre filter & Fine filter
- Mono block pump 1 No.
- Dosing pump 1 No.
- Control Panel
- Pressure Gauge

Advantages




COMPACT UNIT



NO MAJOR CIVIL WORK REQUIRED



USER FRIENDLY



PLUG & PLAY OPERATION



MAINTAINS STATUTORY NORMS

ATS ELGI

Private Industrial Estate, Kurichy,
Coimbatore - 641021, Tamil Nadu, India.

Visit us at : www.ats-elgi.com | Email : enquiry@ats-elgi.com

Toll Free Number : **1800-203-3544**

Follow Us On : [in](#) [f](#) [@](#) [v](#) [t](#)

ATS ELGI authorized dealer